

THE COMMISSIONER OF PATENTS AND TRADEMARKS
Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of Inventor(s)
Marko MASCEK; Michael HENNE

For: PROCESS FOR GENERATING COLLISION SIGNALS

Enclosed are:

- ☒ 2 sheet(s) of drawing(s).
☐ An Assignment of the invention to Robert Bosch GmbH.
☒ A certified copy of German Appln. 196 47 920.7-52 filed November 20, 1996.
☒ A declaration/power of attorney.
☐ An Information Disclosure Statement and form PTO-1449.

The filing fee has been calculated as shown below:

(Col. 1)		(Col. 2)	SMALL ENTITY		OR	OTHER THAN A SMALL ENTITY	
FOR:	NO. FILED	NO. EXTRA	RATE	FEE		RATE	FEE
BASIC FEE				\$395			\$790
TOTAL CLAIMS	6 - 20 =	* 0	x 11	\$		x 22	\$0
INDEP CLAIMS	1 - 3 =	* 0	x 41	\$		x 82	\$0
<input type="checkbox"/> MULTIPLE DEPENDENT CLAIM PRESENTED			x 135	\$		x 270	\$0
			TOTAL	\$		TOTAL	\$790

* If the difference in Col. 1 is less than zero, enter "0" in Col. 2

- ☒ Please charge Deposit Account No. 11-0600 in the amount of \$790.00 to cover the filing fee. A duplicate copy of this sheet is enclosed.
☐ A check to cover the filing fee is enclosed.
☒ The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 11-0600. A duplicate copy of this sheet is enclosed.
☒ Any additional filing fees required under 37 C.F.R. § 1.16.
☒ Any patent application processing fees under 37 C.F.R. § 1.17.
☒ The Commissioner is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. 11-0600. A duplicate copy of this sheet is enclosed.
☒ Any patent application processing fees under 37 C.F.R. § 1.17.
☐ The issue fee set in 37 C.F.R. § 1.18 at or before mailing of the Notice of Allowance, pursuant to 37 C.F.R. § 1.311(b).
☒ Any filing fees under 37 C.F.R. § 1.16 for presentation of extra claims.

Respectfully Submitted,

KENYON & KENYON
ONE BROADWAY
NEW YORK, N.Y. 10004

Richard L. Mayer (Reg. No. 22,490)

Date: 11/4/97

EXPRESS MAIL NO.: EM360379884US

PROCESS FOR GENERATING COLLISION SIGNALS

5 Field Of The Invention

The present invention relates to a process for generating signals which describe various collision events in motor vehicles.

Background Information

10 In the event of a collision, it would be desirable to achieve an optimum, stable triggering response of the installed restraint systems (air bags, seat belts, etc.) for each type of motor vehicle. In other words, the restraint systems should be triggered only when the occupants of the vehicle are actually endangered in a collision, and then the restraints should also be triggered with a very high degree of reliability. Faulty triggering of restraint systems is
15 undesirable because it is very expensive to service the restraint systems; insurance companies in particular have a great interest in preventing faulty triggering of restraint systems as much as possible. Therefore, the algorithm controlling the triggering of restraint systems must be adapted individually to each type of vehicle. Calibration of the triggering algorithm is performed using collision data that reflect the behavior of the vehicle body in a wide variety
20 of collision situations.

There are essentially three categories of collisions - front, side and rear collisions. Rear collisions should not trigger a restraint system, e.g., bumping of vehicles in parking. Rear collisions occur at low vehicle speeds (≤ 15 km/h). The number of actual collisions of a
25 vehicle should be greatly limited for cost reasons. However, to make the triggering algorithm as reliable and stable as possible, it would be desirable to have access to a large number of collision signals that describe a wide variety of different collision situations.

It is known from the conference paper of ASL at SAE, no. 920480 that measured collision
30 data can be used to generate new synthetic collision data by mathematical methods to describe other collision situations. However, the mathematical method used there to derive new collision signals is very complicated and requires a long computation time. Furthermore, the collisions synthesized by the known method have a poor correlation with collisions that

EM36037988445

actually occur.

Summary Of The Invention

An object of the present invention is to provide a process that will make it possible to generate a plurality of new collision signals representing a wide variety of collision situations with minimal use of computing capacity.

This object is achieved due to the fact that a core signal is derived by low-pass filtering from a collision signal actually measured. The core signal is split into several chronologically sequential signal segments, each signal segment is simulated by a transmission function and all the resulting transmission functions are then combined into an overall transmission function. Finally, one or more collision signals are formed by varying at least one parameter of the overall transmission function. The process according to the present invention needs only a single collision signal actually measured to derive a plurality of modified collision signals using a simple mathematical method.

Brief Description Of The Drawings

Figure 1 shows a flow chart for the process for deriving new collision signals according to an exemplary embodiment of the present invention.

Figure 2 shows a collision signal curve.

Detailed Description

To generate new synthetic collision signals, a collision signal is measured in an actual vehicle collision in a first process step 1 according to Figure 1 and stored in the form of ASCII data, for example. Figure 2 shows a collision signal curve measured at a certain location in the vehicle as an example. The collision signal represents the change in acceleration or deceleration (a) measured at one location in the vehicle as a function of time (t) during a collision. It can be seen that at the beginning of a collision, the measured acceleration (a) undergoes very great changes that subside over time. The negative values shown on the ordinate axis of the curve indicate that acceleration (a) is negative here, i.e., the motor vehicle experiences deceleration on impact with another object. Time t is shown in sampling

increments on the abscissa of the curve.

In a second process step 2, a core signal is selected from the measured collision signal. To do so, the measured collision signal is sent through a linear FIR filter (filter with a limited pulse response) that has a low-pass characteristic and a cut-off frequency between 80 and 200 Hz. Due to this filtering, short-period signal peaks are filtered out, leaving a smoothed core signal at the filter output. The signal curve illustrated in Figure 2 is one such core signal filtered out of the measured collision signal. Upstream from the linear FIR filter there may be a non-linear filter (median filter) which eliminates all signal peaks lasting 1 ms or less. The median filter thus performs presmoothing before the linear FIR filter.

The core signal is then split into a plurality of signal segments in process step 3. The boundaries of the individual signal segments, indicated by points in Figure 2, are preferably set so that each signal segment is a pulse from the overall signal curve. To separate the individual pulses, minimums and points of inflection of the signal curve are first determined with the help of known signal sampling methods. A pulse is either between two minimums or between one minimum and one point of inflection. Whether such a pulse represents a suitable signal segment is determined by comparison of the respective pulse with a model pulse. It is advantageous for the model pulse to be a gaussian pulse that can be varied through two parameters. The first parameter is the pulse width ratio on the right and left of the vertical line of symmetry of the pulse at a certain fraction of the overall pulse amplitude. For example, a ratio of 1:5 between the pulse widths on the right and left of the line of symmetry is defined at 75% of the overall pulse amplitude. The second parameter for the model pulse is the ratio between the pulse amplitudes at the edges on both sides of the line of symmetry. This amplitude ratio may be set at 25%, for example. Only when a pulse selected from the signal curve is inside the limits defined by the model pulse with regard to the pulse width ratio and the pulse amplitude ratio is it treated as a suitable signal segment. A pulse that does not meet these prerequisites is added to the next pulse, and together with it, forms a signal segment.

In the next process step 4, each signal segment is simulated by a transmission function in the z plane. This transmission function has the following form, for example:

$$He(z) = \frac{b_0 + b_1 z^{-1} + b_2 z^{-2}}{1 + a_1 z^{-1} + a_2 z^{-2} + a_3 z^{-3}} \quad (1)$$

In this transmission function, $He(z)$, according to equation (1), six coefficients $b_0, b_1, b_2, a_1, a_2, a_3$ are identified for each signal segment.

Then in process step 5, an overall transmission function $Hs(z)$ is formed from all the individual transmission functions $He(z)$ of the signal segments.

This overall transmission function has the following form:

$$Hs(z) = \sum_{i=1}^s \sum_{j=0}^m \sum_{k=0}^n \frac{b_j z^{-j}}{a_k z^{-k}} z^{-li} \quad (2)$$

where i is the running index for the signal segments, where s is the number of segments;

j is the running index for the numerator coefficient b , where m is the order of the numerator coefficients;

k is the running index for the denominator coefficient a , where n is the order of the denominator coefficient; and

l is a segment vector that runs from one segment to the next and indicates the sampling step at which the respective segment whose transmission function is to be added to the overall transmission function begins.

In process step 6, new collision signals are generated by parameter variations of the overall transmission function $Hs(z)$. Parameter variation means that coefficients a in the overall transmission function are varied. In the transmission function $He(z)$ selected here, coefficients a of the denominator of the overall transmission function $Hs(z)$ form a third-order polynomial in the complex z plane. The roots of this polynomial are the poles of the overall transmission function. Since this is a third-order polynomial, there is a real pole and a

conjugated complex pole pair. New collision signal curves are obtained by varying the locus of at least one complex pole within a circle with radius 1 in the complex z plane (a circle with radius 1 describes the stability limit).

5 Variation of the zero positions, i.e., coefficients b in the numerator, is of no use because it has no effect on the frequency spectrum of the overall transmission function $H_s(z)$ but instead it affects only its amplitude. This variation would create only new collision signals with a varied amplitude but would not alter the shape of the collision signals.

10 The measure of the variation of the denominator coefficients a of the overall transmission function $H_s(z)$ to generate new collision signals that are as realistic as possible is based on calculations of the correlation and the energy deviation (deviation in effective values) between synthetic collision signals and real collision signals. Experience indicates that variations of 0.1% to 1.0% lead to synthetic collision signals having a close correlation with
15 real collisions.

In deviation from the embodiment described above, an even higher-order transmission function can be used instead of a third-order transmission function. Likewise, even a second-order transmission function can be used.

20 The process on which the present invention is based makes it possible to derive new collision signals from core signals with a rather high filter cut-off frequency of up to 200 Hz. This guarantees that important information on the collision signal actually measured is preserved in generating synthetic collision signals.

25 The collision signal actually measured is composed of the core signal selected by filtering and a residual signal. The residual signal can also be varied and superimposed on the varied core signal to synthesize new collision signals.

What Is Claimed Is:

1. A process for generating at least one descriptive collision signal describing motor vehicle collisions, comprising the steps of:
deriving a core signal by low-pass filtering a collision signal actually measured;
splitting the core signal into a plurality of chronologically sequential signal segments;
simulating each of the signal segments using a respective transmission function;
combining the transmission functions to form an overall transmission function; and
forming the at least one descriptive collision signal by varying at least one parameter of the overall transmission function.
2. The process according to claim 1, wherein the core signal is split into individual pulses.
3. The process according to claim 2, further comprising the step of determining the signal segments by comparing the individual pulses with a model pulse, and accepting one of the individual pulses as an individual signal segment when the individual pulse is within preset limits relative to the model pulse, the model pulse being a gaussian pulse, the gaussian pulse being variable through a plurality of parameters.
4. The process according to claim 1, wherein the signal segments are simulated using the transmission function in a complex z plane in the following manner:

$$He(z) = \frac{b0 + b1z^{-1} + b2z^{-2}}{1 + a1z^{-1} + a2z^{-2} + a3z^{-3}}$$

wherein b0, b1, b2, a1, a2, and a3 are coefficients identified for the signal segments.

5. The process according to claim 1, wherein the overall transmission function is determined in the following manner:

$$Hs(z) = \sum_{i=1}^s \sum_{j=0}^m \sum_{k=0}^n \frac{bjz^{-1}}{akiz^{-k}} z^{-ti}$$

wherein i is a running index for the signal segments, with s being a number of signal segments;

j is a running index for a numerator coefficient b , with m being an order of the numerator coefficient;

k is a running index for a denominator coefficient a , with n being an order of the denominator coefficient; and

l is a vector denoting boundaries of the signal segments.

6. The process according to claim 5, wherein at least one complex pole in the overall transmission function is varied to form the at least one descriptive collision signal.

Abstract Of The Disclosure

5 A relatively uncomplicated process for generating collision signals that describe various collision processes involving motor vehicles. The process involves deriving a core signal by low-pass filtering from a collision signal actually measured, splitting this core signal into several signal segments, simulating each signal segment by a transmission function, then combining all the transmission functions into one overall transmission function, and forming one or more new collision signals by varying at least one parameter of the overall transmission function.

141086-1

464047 " 02/06/83




Fig. 1

02/22/80




Fig. 2

COMBINED DECLARATION AND
POWER OF ATTORNEY FOR PATENT APPLICATION

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below adjacent to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled "PROCESS FOR GENERATING COLLISION SIGNALS," and the specification of which:

- ☒ is attached hereto;
- ☐ was filed as United States Application Serial No. _____ on _____, 19__ and was amended by the Preliminary Amendment filed on _____, 19__.
- ☐ was filed as _____ Application Number _____, on the ____ day of _____, ____.
- ☐ an English translation of which is filed herewith.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, §1.56(a). I hereby claim foreign priority benefits under Title 35, United States Code § 119 of any foreign application(s) for patent or inventor's certificate or of any PCT international applications(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least

EM36037988445

one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

**PRIOR FOREIGN/PCT APPLICATION(S)
AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. § 119**

Country : Federal Republic of Germany

Application No. : 1 96 47 920.7-52

Date of Filing: November 20, 1996

Priority Claimed

Under 35 U.S.C. § 119 : ☒ Yes ☐ No

I hereby claim the benefit under Title 35, United States Code § 120 of any United States Application or PCT International Application designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations § 1.56(a) which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application:

**PRIOR U.S. APPLICATIONS OR
PCT INTERNATIONAL APPLICATIONS
DESIGNATING THE U.S. FOR BENEFIT UNDER 35 U.S.C. § 120**

U.S. APPLICATIONS

Number :

Filing Date :

**PCT APPLICATIONS
DESIGNATING THE U.S.**

PCT Number :

PCT Filing Date :

I hereby appoint the following attorney(s)
and/or agents to prosecute the above-identified
application and transact all business in the Patent and
Trademark Office connected therewith.

(List name(s) and registration number(s)):

Richard L. Mayer,	Reg. No. 22,490
Gerard A. Messina,	Reg. No. 35,952
_____,'	Reg. No. _____
_____,'	Reg. No. _____

All correspondence should be sent to:

Richard L. Mayer, Esq.
Kenyon & Kenyon
One Broadway
New York, New York 10004

Telephone No.: (212) 425-7200
Facsimile No.: (212) 425-5288

I hereby declare that all statements made
herein of my own knowledge are true and that all
statements made on information and belief are believed to
be true and further that these statements were made with
the knowledge that willful false statements and the like
so made are punishable by fine or imprisonment or both
under Section 1001 of Title 18 of the United States Code
and that such willful false statements may jeopardize the
validity of the application or any patent issuing
thereon.

Full name of first inventor Marko MASCEK

Inventor's signature *Marko* Date 05/10/97

Citizenship German

Residence Queen's College

CB39ET Cambridge

United Kingdom

Post Office Address Same as above

SECRET

5 of 5

Full name of second inventor Michael HENNE

Inventor's signature *[Signature]* Date 8/10/97

Citizenship German

Residence Schillerstrasse 33

74374 Zaberfeld

Federal Republic of Germany

Post Office Address Same as above

141270-1

141270-1